

---

<b>Description:</b>	Patented Premium Engineered COREtec Plus Design™ Luxury Vinyl Plank & Tile Floating Floor with Attached Cork Underlayment
<b>Warranty:</b>	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 10 Year Limited Commercial Wear Warranty
<b>Installation:</b>	Float, Glue Down
<b>Size/Packaging:</b>	<b>Multi-Width Planks</b>  5" x 36" x 8 mm Planks 7" x 72" x 8 mm Planks 9" x 72" x 8 mm Planks 20.971 sq. ft./carton, 8 planks per carton, 34.17 lbs. each carton, 72 ctns per pallet  5" x 36" x 8 mm Planks 7" x 72" x 8 mm Planks 9" x 72" x 8 mm Planks 28.062 sq. ft./carton, 10 planks per carton, 45.86 lbs. each carton, 54 ctns per pallet  7" x 72" x 8 mm Planks 21.274 sq. ft./carton, 12 planks per carton, 34.17 lbs. each carton, 60 ctns per pallet  <b>Multi-Tone Planks</b>  5" x 48" x 8 mm Planks 30.256 sq. ft./carton, 18 planks per carton, 49.60 lbs. each carton, 28 ctns per pallet  <b>Multi-Tone Tiles</b>  12" x 36" x 8 mm Tiles 23.847 sq. ft./carton, 8 planks per carton, 39.68 lbs. each carton, 30 ctns per pallet  18" x 24" x 8 mm Tiles 23.847 sq. ft./carton, 8 planks per carton, 39.68 lbs. each carton, 30 ctns per pallet  <b>Multi-Width and Multi-Tone Tiles</b>  6" x 24" x 8 mm Tiles 12" x 24" x 8 mm Tiles 29.32 sq. ft./carton, 20 planks per carton, 48.50 lbs. each carton, 28 ctns per pallet
<b>Construction:</b>	1.7 mm virgin PVC (0.5 mm/20 mil wear surface) 5.0 mm core (Limestone, virgin PVC, wood and bamboo dust). 1.5 mm cork underlayment
<b>Wear Finish:</b>	2 coats UV-cured acrylic
<b>Gloss Level:</b>	2% - 6%

**TEST DATA**

<b>ASTM-E648 Critical Radiant Flux:</b>	Meets or exceeds, Class 1
<b>ASTM E492-09 Impact Sound Conduction:</b>	IIC 62 db
<b>ASTM E90-09 Airborne Sound Conduction:</b>	STC 62 db
<b>ASTM C518 Thermal Resistance:</b>	R Value – 0.57
<b>NALFA 3.2 Thickness Swell:</b>	Class 4, Heavy Commercial
<b>NALFA 3.3 Xenon Light Resistance:</b>	Class 4, Heavy Commercial
<b>NALFA 3.4 Cleanability-Stain Resistance:</b>	Class 4, Heavy Commercial
<b>NALFA 3.5 Large Ball Impact Resistance:</b>	Class 4, Heavy Commercial
<b>NALFA 3.6 Small Ball Impact Resistance:</b>	Class 4, Heavy Commercial
<b>NALFA 3.8 Dimensional Tolerance:</b>	Class 4, Heavy Commercial
<b>NALFA 3.9 Caster Chair:</b>	Class 3, Commercial
<b>NALFA 3.10 Surface Bonding:</b>	1.31 N/mm – Exceeds Class 3 Commercial Requirement
<b>ASTM C 1028-96 Static Coefficient of Friction:</b>	0.68 (slip resistance) Passes ADA/OSHA standard
<b>ASTM F-970-07 Static Load Limit:</b>	0.004 inch – Passes at 250 psi
<b>ASTM-F2753 Rolling Load Over Resilient FC:</b>	0.024 inch
<b>ASTM F 1514 Color Resistance to Heat:</b>	Meets <8.0 Delta E Requirement
<b>ASTM F 1515 Color Resistance to Light:</b>	Meets <8.0 Delta E Requirement

**Certifications:** CARB Compliant  
 GREENGUARD GOLD Certified

**Environmental Statement:** USFloors' commitment is to provide consumers and specifiers with beautiful and durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. USFloors is a member of the USGBC.

**Country of Origin:** Manufactured in China