



COREtec Pro Plus Enhanced

Technical Specifications

Description:	Engineered COREtec Pro Plus Enhanced Floating Floor with Attached Cork Underlayment
Warranty:	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 15 Year Limited Commercial Wear Warranty
Installation:	Float, Glue Down
Size/Packaging:	7.13" x 48.03" x 7 mm Planks 19.02 sq. ft./carton, 8 planks per carton, 48.94 lbs. per carton, 40 cartons per pallet 18.50" x 24.02" x 7 mm Tiles 24.69 sq. Ft./carton, 8 tiles per carton, 55.12 lbs. per carton, 36 cartons per pallet
Density:	1900 kg/m3
Pattern Repeat:	5 planks 4 tiles
Construction:	0.5 mm/20 mil wear surface 5.6 mm rigid core 1.4 mm cork underlayment
Edges/Ends:	Painted Bevel
Wear Finish:	UV-cured acrylic
Gloss Level:	8% - 10%

TEST DATA

ASTM E492-09 Impact Sound Conduction: STC 50 db
ASTM E90-09 Airborne Sound Conduction: IIC 54 db
ASTM F-970-15 Static Load Limit: <.005" at 250 lbs
ASTM F2199 Dimensional Stability: Pass
ASTM F1914 Short-Term Indentation: Pass
ASTM-E648-15 Critical Radiant Flux: Class 1

ASTM-E662-17 Smoke Density: <450 Flaming and Non Flaming Modes

Certifications:	GREENGUARD GOLD Certified
Environmental Statement:	COREtec's commitment is to provide consumers and specifiers with beautiful and durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. COREtec is a member of the USGBC.
Country of Origin:	Manufactured in China